

ABC STORED PRESSURE

Capacity : 1kg



- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 8 - 12 sec.
- Range: 2Mtr.
- Rating: 1A - 8B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Filled with MAP powder
- Design as per IS: 15683

Capacity : 2kg



- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 8 - 12 sec.
- Range: 2Mtr.
- Rating: 1A - 8B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Filled with MAP powder
- Design as per IS: 15683

Capacity : 4kg



- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 4Mtr.
- Rating: 2A - 21B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Filled with MAP powder
- Design as per IS: 15683

Capacity : 6kg



- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 4Mtr.
- Rating: 3A - 34B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Filled with MAP powder
- Design as per IS: 15683



Capacity : 9kg

- Temperature Range: -20°C To + 55°C
- Discharge 85% & Duration: 15 - 20 sec.
- Range: 5Mtr.
- Rating: 4A - 55B

PERFORMANCE & FEATURES

- Hand Controlled Discharge
- Nitrogen Gas Propellant
- Pressure Indicator Pressure Gauge
- Weather Resistance Epoxy
- Polyester base powder
- Filled with MAP powder
- Design as per IS: 15683

